

Request for Quotation No.	RFQ-2024.03.28-A
Opening Date	28.03.2024
Closing Date	16.04.2024
Credit Limit	30 days

Request for Quotation

Sub: Request for Price Quotation for Mentioned Items for mPower USAID CNHA Project.

Please be competitive while pricing and provide the sealed quotation of the following items as per the given requirements under the terms and conditions mentioned below on your respective Letterhead pads in favor of **mPower Social Enterprises Limited**.

SL	Items	Description	Unit Required																																																																														
01	SERVER	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Module Name</th> <th style="text-align: left;">Option Name</th> <th style="text-align: center;">Qty</th> </tr> </thead> <tbody> <tr> <td>Brand</td> <td>Any Brand</td> <td></td> </tr> <tr> <td>Base</td> <td>Latest Model</td> <td style="text-align: center;">1</td> </tr> <tr> <td>FRONT STORAGE</td> <td>Chassis with up to 8x2.5" Drives</td> <td style="text-align: center;">1</td> </tr> <tr> <td>BACKPLANE</td> <td>SAS/SATA Backplane</td> <td style="text-align: center;">1</td> </tr> <tr> <td>CPU CONFIGURATION</td> <td>2 CPU Configuration</td> <td style="text-align: center;">1</td> </tr> <tr> <td>Trusted Platform Module</td> <td>Trusted Platform Module 2.0 V3</td> <td style="text-align: center;">1</td> </tr> <tr> <td>Chassis Configuration</td> <td>2.5" Chassis with up to 8 Hard Drives (SAS/SATA), 2 CPU, V3</td> <td style="text-align: center;">1</td> </tr> <tr> <td>Processor</td> <td>Intel® Xeon® Silver 4310 2.1G, 12C/24T, 10.4GT/s, 18M Cache, Turbo, HT (120W) DDR4-2666</td> <td style="text-align: center;">2</td> </tr> <tr> <td>Processor Thermal Configuration</td> <td>Standard Heatsink for 2 CPU configuration</td> <td style="text-align: center;">1</td> </tr> <tr> <td>Memory Configuration Type</td> <td>Performance Optimized</td> <td style="text-align: center;">1</td> </tr> <tr> <td>Memory DIMM Type and Speed</td> <td>3200MT/s RDIMMs</td> <td style="text-align: center;">1</td> </tr> <tr> <td>Memory Capacity</td> <td>64GB RDIMM, 3200MT/s, Dual Rank, 16Gb</td> <td style="text-align: center;">8</td> </tr> <tr> <td>RAID Configuration</td> <td>C7, Unconfigured RAID for HDDs or SSDs (Mixed Drive Types Allowed)</td> <td style="text-align: center;">1</td> </tr> <tr> <td>RAID/Internal Storage Controllers</td> <td>Front PERC H755 Rear Load</td> <td style="text-align: center;">1</td> </tr> <tr> <td>Hard Drives</td> <td>2.4TB 10K RPM SAS ISE 12Gbps 512e 2.5in Hot-plug Hard Drive</td> <td style="text-align: center;">4</td> </tr> <tr> <td>BIOS and Advanced System Configuration Settings</td> <td>Performance BIOS Setting</td> <td style="text-align: center;">1</td> </tr> <tr> <td>Advanced System Configurations</td> <td>UEFI BIOS Boot Mode with GPT Partition</td> <td style="text-align: center;">1</td> </tr> <tr> <td>Fans</td> <td>Standard Fan x5</td> <td style="text-align: center;">1</td> </tr> <tr> <td>Power Supply</td> <td>Dual, Hot-plug, Power Supply Fault Tolerant Redundant (1+1), 800W, Mixed Mode,NAF</td> <td style="text-align: center;">1</td> </tr> <tr> <td>Power Cords</td> <td>Jumper Cord - C13/C14, 4M, 250V, 10A (US, EU, TW, APCC countries except ANZ)</td> <td style="text-align: center;">2</td> </tr> <tr> <td>PCIe Riser</td> <td>Riser Config 0, Half Length, Low Profile, 5x16 + 1x4 slots</td> <td style="text-align: center;">1</td> </tr> <tr> <td>Motherboard</td> <td>Motherboard with Broadcom 5720 Dual Port 1Gb On- Board LOM</td> <td style="text-align: center;">1</td> </tr> <tr> <td>Ethernet Mezzanine Adapters</td> <td>Broadcom 5720 Quad Port 1GbE BASE-T Adapter, OCP NIC 3.0</td> <td style="text-align: center;">1</td> </tr> <tr> <td>Bezel</td> <td>2U LCD Bezel</td> <td style="text-align: center;">1</td> </tr> <tr> <td>Embedded Systems Management (Multi)</td> <td>OpenManage Enterprise Advanced</td> <td style="text-align: center;">1</td> </tr> </tbody> </table>	Module Name	Option Name	Qty	Brand	Any Brand		Base	Latest Model	1	FRONT STORAGE	Chassis with up to 8x2.5" Drives	1	BACKPLANE	SAS/SATA Backplane	1	CPU CONFIGURATION	2 CPU Configuration	1	Trusted Platform Module	Trusted Platform Module 2.0 V3	1	Chassis Configuration	2.5" Chassis with up to 8 Hard Drives (SAS/SATA), 2 CPU, V3	1	Processor	Intel® Xeon® Silver 4310 2.1G, 12C/24T, 10.4GT/s, 18M Cache, Turbo, HT (120W) DDR4-2666	2	Processor Thermal Configuration	Standard Heatsink for 2 CPU configuration	1	Memory Configuration Type	Performance Optimized	1	Memory DIMM Type and Speed	3200MT/s RDIMMs	1	Memory Capacity	64GB RDIMM, 3200MT/s, Dual Rank, 16Gb	8	RAID Configuration	C7, Unconfigured RAID for HDDs or SSDs (Mixed Drive Types Allowed)	1	RAID/Internal Storage Controllers	Front PERC H755 Rear Load	1	Hard Drives	2.4TB 10K RPM SAS ISE 12Gbps 512e 2.5in Hot-plug Hard Drive	4	BIOS and Advanced System Configuration Settings	Performance BIOS Setting	1	Advanced System Configurations	UEFI BIOS Boot Mode with GPT Partition	1	Fans	Standard Fan x5	1	Power Supply	Dual, Hot-plug, Power Supply Fault Tolerant Redundant (1+1), 800W, Mixed Mode,NAF	1	Power Cords	Jumper Cord - C13/C14, 4M, 250V, 10A (US, EU, TW, APCC countries except ANZ)	2	PCIe Riser	Riser Config 0, Half Length, Low Profile, 5x16 + 1x4 slots	1	Motherboard	Motherboard with Broadcom 5720 Dual Port 1Gb On- Board LOM	1	Ethernet Mezzanine Adapters	Broadcom 5720 Quad Port 1GbE BASE-T Adapter, OCP NIC 3.0	1	Bezel	2U LCD Bezel	1	Embedded Systems Management (Multi)	OpenManage Enterprise Advanced	1	01 Pc
		Module Name	Option Name	Qty																																																																													
		Brand	Any Brand																																																																														
		Base	Latest Model	1																																																																													
		FRONT STORAGE	Chassis with up to 8x2.5" Drives	1																																																																													
		BACKPLANE	SAS/SATA Backplane	1																																																																													
		CPU CONFIGURATION	2 CPU Configuration	1																																																																													
		Trusted Platform Module	Trusted Platform Module 2.0 V3	1																																																																													
		Chassis Configuration	2.5" Chassis with up to 8 Hard Drives (SAS/SATA), 2 CPU, V3	1																																																																													
		Processor	Intel® Xeon® Silver 4310 2.1G, 12C/24T, 10.4GT/s, 18M Cache, Turbo, HT (120W) DDR4-2666	2																																																																													
		Processor Thermal Configuration	Standard Heatsink for 2 CPU configuration	1																																																																													
		Memory Configuration Type	Performance Optimized	1																																																																													
		Memory DIMM Type and Speed	3200MT/s RDIMMs	1																																																																													
		Memory Capacity	64GB RDIMM, 3200MT/s, Dual Rank, 16Gb	8																																																																													
		RAID Configuration	C7, Unconfigured RAID for HDDs or SSDs (Mixed Drive Types Allowed)	1																																																																													
		RAID/Internal Storage Controllers	Front PERC H755 Rear Load	1																																																																													
		Hard Drives	2.4TB 10K RPM SAS ISE 12Gbps 512e 2.5in Hot-plug Hard Drive	4																																																																													
		BIOS and Advanced System Configuration Settings	Performance BIOS Setting	1																																																																													
		Advanced System Configurations	UEFI BIOS Boot Mode with GPT Partition	1																																																																													
		Fans	Standard Fan x5	1																																																																													
		Power Supply	Dual, Hot-plug, Power Supply Fault Tolerant Redundant (1+1), 800W, Mixed Mode,NAF	1																																																																													
Power Cords	Jumper Cord - C13/C14, 4M, 250V, 10A (US, EU, TW, APCC countries except ANZ)	2																																																																															
PCIe Riser	Riser Config 0, Half Length, Low Profile, 5x16 + 1x4 slots	1																																																																															
Motherboard	Motherboard with Broadcom 5720 Dual Port 1Gb On- Board LOM	1																																																																															
Ethernet Mezzanine Adapters	Broadcom 5720 Quad Port 1GbE BASE-T Adapter, OCP NIC 3.0	1																																																																															
Bezel	2U LCD Bezel	1																																																																															
Embedded Systems Management (Multi)	OpenManage Enterprise Advanced	1																																																																															



		Embedded Systems Management (Multi)	iDRAC9, Enterprise 15G	1																																																											
		Quick Sync	Quick Sync 2 (At-the-box mgmt)	1																																																											
		Password	iDRAC,Factory Generated Password	1																																																											
		iDRAC Server Manager	iDRAC Service Module (ISM), NOT Installed	1																																																											
		Group Manager	iDRAC Group Manager, Enabled	1																																																											
		Rack Rails	ReadyRails Sliding Rails with Cable Management Arm	1																																																											
		PDU Unit	10 Port Aluminum PDU For Server Rack	1																																																											
		Services: Hardware Support	Basic Next Business Day 36Months-ACDTS, 36 Month(s)	1																																																											
		Services: Extended Service	ProSupport and Next Business Day Onsite Service-ACDTS, 36 Month(s)	1																																																											
02	ONLINE UPS 10 KVA	<table border="1"> <tr> <td>BRAND</td> <td>Any Brand</td> </tr> <tr> <td>MODEL</td> <td>Any Model</td> </tr> <tr> <td>Capacity:</td> <td>10KVA</td> </tr> <tr> <td colspan="2">INPUT RECTIFIER</td> </tr> <tr> <td>Rated Voltage</td> <td>230V (1Ph)</td> </tr> <tr> <td>Voltage tolerance</td> <td>160V to 300V</td> </tr> <tr> <td>Frequency</td> <td>50 / 60 Hz</td> </tr> <tr> <td>Power Factor</td> <td>0.99 Constant</td> </tr> <tr> <td>Total Harmonic Distortion</td> <td><3%</td> </tr> <tr> <td colspan="2">OUTPUT INVERTER</td> </tr> <tr> <td>Voltage</td> <td>208/220/230/240 V</td> </tr> <tr> <td>Voltage Tolerance</td> <td>±1 %</td> </tr> <tr> <td>Frequency</td> <td>50 / 60 Hz (46÷54Hz/56÷64Hz)</td> </tr> <tr> <td>Overload Capability</td> <td>Up to 130% for 1 minute</td> </tr> <tr> <td>Crest Factor</td> <td>3:1</td> </tr> <tr> <td colspan="2">EFFICIENCY</td> </tr> <tr> <td>Online mode</td> <td>90%</td> </tr> <tr> <td>In ECO-MODE configuration</td> <td>98%</td> </tr> <tr> <td>Transfer Time</td> <td>0 (Zero) millisecond</td> </tr> <tr> <td>Current Waveform</td> <td>100% Pure Sine Wave</td> </tr> <tr> <td>Battery Type</td> <td>100% Sealed Maintenance free Lead Acid</td> </tr> <tr> <td>Protection</td> <td>Overload, short circuit, over voltage, under voltage, temperature, low voltage</td> </tr> <tr> <td colspan="2">COMMUNICATION</td> </tr> <tr> <td>Interfaces</td> <td>RS232 - USB</td> </tr> <tr> <td>ENVIRONMENT</td> <td>0°C to 40°C (15°C to 22°C for maximum Battery Life) Related Humidity: 0%-95% without condensation</td> </tr> <tr> <td>FEATURE</td> <td>Communication Capability, Microprocessor Controlled, Absolute Battery Protection, Built In Avr, Backup Time Expandable.</td> </tr> <tr> <td>Standards</td> <td>(EN)IEC 62040-1-1(For Safety), (EN)IEC 62040-3(For performance & topology, VFI-ss-111), EN 50091-2/IEC 62040-2(EMC Standard), IEC 60950-1-1(tasted by the TUV), Product Certification: CE IP rating: IP 20 (compliant with IEC 60529)</td> </tr> <tr> <td>Certificate</td> <td>ISO 9001:2008, BSI, CE.</td> </tr> <tr> <td>Battery</td> <td>Back-up Time: 60 Minutes (Full Load) Battery Capacity: 12V x 40Ah Quantity: 20 Units Brand: Equivalent Origin: WITH POWERFUL BATTERY CHARGER FOR LONG BACKUP Installation, Commissioning & Testing One year Warranty including Spare Parts & Battery</td> </tr> </table>			BRAND	Any Brand	MODEL	Any Model	Capacity:	10KVA	INPUT RECTIFIER		Rated Voltage	230V (1Ph)	Voltage tolerance	160V to 300V	Frequency	50 / 60 Hz	Power Factor	0.99 Constant	Total Harmonic Distortion	<3%	OUTPUT INVERTER		Voltage	208/220/230/240 V	Voltage Tolerance	±1 %	Frequency	50 / 60 Hz (46÷54Hz/56÷64Hz)	Overload Capability	Up to 130% for 1 minute	Crest Factor	3:1	EFFICIENCY		Online mode	90%	In ECO-MODE configuration	98%	Transfer Time	0 (Zero) millisecond	Current Waveform	100% Pure Sine Wave	Battery Type	100% Sealed Maintenance free Lead Acid	Protection	Overload, short circuit, over voltage, under voltage, temperature, low voltage	COMMUNICATION		Interfaces	RS232 - USB	ENVIRONMENT	0°C to 40°C (15°C to 22°C for maximum Battery Life) Related Humidity: 0%-95% without condensation	FEATURE	Communication Capability, Microprocessor Controlled, Absolute Battery Protection, Built In Avr, Backup Time Expandable.	Standards	(EN)IEC 62040-1-1(For Safety), (EN)IEC 62040-3(For performance & topology, VFI-ss-111), EN 50091-2/IEC 62040-2(EMC Standard), IEC 60950-1-1(tasted by the TUV), Product Certification: CE IP rating: IP 20 (compliant with IEC 60529)	Certificate	ISO 9001:2008, BSI, CE.	Battery	Back-up Time: 60 Minutes (Full Load) Battery Capacity: 12V x 40Ah Quantity: 20 Units Brand: Equivalent Origin: WITH POWERFUL BATTERY CHARGER FOR LONG BACKUP Installation, Commissioning & Testing One year Warranty including Spare Parts & Battery	01 Pc
BRAND	Any Brand																																																														
MODEL	Any Model																																																														
Capacity:	10KVA																																																														
INPUT RECTIFIER																																																															
Rated Voltage	230V (1Ph)																																																														
Voltage tolerance	160V to 300V																																																														
Frequency	50 / 60 Hz																																																														
Power Factor	0.99 Constant																																																														
Total Harmonic Distortion	<3%																																																														
OUTPUT INVERTER																																																															
Voltage	208/220/230/240 V																																																														
Voltage Tolerance	±1 %																																																														
Frequency	50 / 60 Hz (46÷54Hz/56÷64Hz)																																																														
Overload Capability	Up to 130% for 1 minute																																																														
Crest Factor	3:1																																																														
EFFICIENCY																																																															
Online mode	90%																																																														
In ECO-MODE configuration	98%																																																														
Transfer Time	0 (Zero) millisecond																																																														
Current Waveform	100% Pure Sine Wave																																																														
Battery Type	100% Sealed Maintenance free Lead Acid																																																														
Protection	Overload, short circuit, over voltage, under voltage, temperature, low voltage																																																														
COMMUNICATION																																																															
Interfaces	RS232 - USB																																																														
ENVIRONMENT	0°C to 40°C (15°C to 22°C for maximum Battery Life) Related Humidity: 0%-95% without condensation																																																														
FEATURE	Communication Capability, Microprocessor Controlled, Absolute Battery Protection, Built In Avr, Backup Time Expandable.																																																														
Standards	(EN)IEC 62040-1-1(For Safety), (EN)IEC 62040-3(For performance & topology, VFI-ss-111), EN 50091-2/IEC 62040-2(EMC Standard), IEC 60950-1-1(tasted by the TUV), Product Certification: CE IP rating: IP 20 (compliant with IEC 60529)																																																														
Certificate	ISO 9001:2008, BSI, CE.																																																														
Battery	Back-up Time: 60 Minutes (Full Load) Battery Capacity: 12V x 40Ah Quantity: 20 Units Brand: Equivalent Origin: WITH POWERFUL BATTERY CHARGER FOR LONG BACKUP Installation, Commissioning & Testing One year Warranty including Spare Parts & Battery																																																														



03	LAPTOP	<p>Processor Brand- Intel Processor Model- Intel Core i7-1355U (up to 5.0GHz, 12 MB L3 cache) Generation-13th Gen Processor Frequency- Up to 4.40 GHz Processor Thread- 12, CPU Cache- 12 MB L3 cache Display Size**- 14-inch Display Resolution- FHD (1920 x 1080) RAM-16GB, RAM Type-DDR4 Storage Capacity- 512 SSD WebCam-720p HD Bag: 01 Carry bag Battery Type- Long Life 3-cell, Li-ion Battery Capacity- 51 Wh Warranty-</p>	08 Pcs
03	LAPTOP	<p>Processor Brand- Intel Processor Model- Intel Core i7-1355U (up to 5.0GHz, 12 MB L3 cache) Generation-13th Gen Processor Frequency- Up to 4.40 GHz Processor Thread- 12, CPU Cache- 12 MB L3 cache Display Size**- 15.6-inch Display Resolution- FHD (1920 x 1080) RAM-16GB, RAM Type-DDR4 Storage Capacity- 512 SSD WebCam-720p HD Battery Type- Long Life 3-cell, Li-ion Battery Capacity- 51 Wh Bag: 01 Carry bag Warranty-</p>	06 Pcs
04	PRINTER	<p>Functions - Print Only Output Color - Black & White Print Speed (Black) - Up to 40ppm (ISO) Print Speed (Color) - No Paper Size Max. -A4, Legal Interface (Built-in) - USB, LAN, WiFi Duplex- Automatic Warranty-</p>	01 Pc
06	SMART PHONE	<p>Dimension- 160.1 X 76.8 X 8.4 mm Weight-200g SIM- Dual SIM (Nano-SIM, dual stand-by) Size-6.5 inches Resolution-1080 x 2408 pixels OS- Android 13, One UI 4.1 Chipset- Snapdragon 750G, 8nm Rear Camera- 50.0 MP 5.0 MP (Ultrawide) 2.0 MP (Macro) RAM-6 GB, Internal Storage-128GB Capacity- 5000 mAh Colors- Black Network- 5G Warranty-</p>	09 Pcs
07	SMART TABLETS	<p>Display: 8-inch HD (1280x800) IPS CPU: MediaTek Helio A22, 2.3 GHz Octa-Core (12 nm) RAM: 3GB LPDDR4x, Storage: 32GB eMMC 5.1 Battery: 5100mAh, Supports 10W Fast Charging Connectivity-4G LTE, 3G, 2G Operating System-Android 13 Warranty-</p>	04 Pcs



08	FURNITURE (Office Chair)	<p><u>OFFICE CHAIR</u></p> <ul style="list-style-type: none"> ○ Made from superior quality chrome plated mild steel. ○ Color will be confirmed after selection of the chair. ○ L570 X W 540 X SH 445-540 X BH1240 MM ○ High quality fabric upholstery with soft and durable cushioning. Fabric can be selected from available options. ○ Metal Inert Gas (MIG) welding for superior quality and durability ○ Cutting and bending are done by latest Japanese CNC machine with 99.99% accuracy ○ Imported high quality hardware fittings ○ Indoor use only ○ 01 Years Service Warranty 	23 Pcs
-----------	-------------------------------------	--	---------------

Terms & Conditions:


1. **QUOTATION:** All quotations must be printed in the company letterhead pad, and submitted in a hard or soft copy within the specified time mentioned. You can submit quotations for a single or multiple items from the list above according to the nature of your business.
2. **PROFILE:** A brief Company Profile must be attached along with the quotation.
3. **SUBMISSION:** Please send your **Cover Letter, Organizational Profile, Financial Offer, and Other Related Documents- Updated Trade License, TIN, BIN, Tax Return Acknowledgement Slip or Certificate**, Hard Copy or Soft Copy submissions will be welcomed by **1700 hours of 16th April of 2024**.
4. **DELIVERY:** If selected, delivery must be in strict compliance with the schedule contained in the Order. All goods to be delivered from ready stock hereunder shall be packaged to ensure safe arrival at their destination, to secure the best transportation means and to comply with the requirements of common carriers to given delivery at mPower office (10th floor), if selected.
5. **RETURN:** mPower Social Enterprises Limited holds all rights to return any product at the time of delivery to up to 10 days, given the delivered product is faulty or defective.
6. **PAYMENT:** Account payee cheque with **30 days credit facility** upon delivery.
7. **WARRANTY:** Seller must Provide **SERVICE & WARRANTY** for all of the Products.
8. **TAX & VAT:** Will be deducted at source as per government policy (If applicable).
9. **VAT:** If the Vendor adds the VAT amount in the price quotation, then mPower will provide VAT Coupon for the Vat amount.
10. **Vendor Enlistment Notice & Form:** Please note that before submitting your respective quotations you are requested to use the google drive link below to access our vendor enrollment form and enlist your organization as our vendor then submit your respective quotations accordingly.

The link to the vendor enrollment form:
<https://drive.google.com/drive/folders/1cGQSjzerBLzaYJiWgK1dn5U2NML-SOp6?usp=sharing>

As per our Vendor Enrollment Notice (REF-2024-01-01-A) and Vendor Enrollment Form (VEN-24-M1) links, you are requested to complete and return the form mentioned in the notice. with all necessary documents (Section 9). All documents are to be submitted in hard copy in a sealed envelope or soft copy by email.
11. In case of hard copy submission, you are requested to submit your quotations with relevant documents in a sealed envelope in our office located at **Nur Empori (Level-10), House-77, Road-11, Block-M, Banani, Dhaka-1213**. In case of soft copy submission, you need to send your quotations with relevant documents from the official email address of your organization to the following address: info@mpower-social.com

Looking forward to a healthy and prosperous business relationship with you in the coming days.

Thanking You,



Akib Hossain Omi
 Head of Internal Operations
 mPower Social Enterprises Limited
 Email: akib@mpower-social.com
 Mobile: 01677179669

